

TAMSTUCCO POLVERE

POWDER FILLER

code 9410110

DESCRIPTION

TAMSTUCCO POLVERE is a filler for interior use for levelling imperfections both on woodwork and walls.

The product can be used to fill even cracks and depressions, making the surface even.

TAMSTUCCO POLVERE is easy to sand, assures a good base for paints to adhere to and features good adhesion.

INSTRUCTIONS FOR USE

May be applied on:

- New and old plasters based on hydraulic binders.
- Concrete surfaces.
- Gypsum and gypsumboard surfaces.
- Old paints and wall coatings that are organic or mineral in nature, dry, compact, absorbent and cohesive.
- Mineral conglomerates of various kinds, as long as they are absorbent.
- Interior woodwork, before a covering painting system is employed.

TAMSTUCCO POLVERE is a primer and must be painted over with a top coat finishing system.

TECHNICAL SPECIFICATIONS

-Type of Binder: fast-drying gypsum, retarders and setting regulators

-Appearance: white powder

-Drying time (at 25 C and 65% R.H.): to sand after 3-4 hours; to recoat after 6 hours.

COATABILITY: with all SAN MARCO emulsion paints.

PREPARING THE SURFACE

Plaster:

- Make sure that the surface has a maturing time of at least 28 days.

- Check the state of repair. The surface must be consistent. If this is not the case, take measures to reconstruct and strengthen the surface using specific products.

- Remove any efflorescence by buffing or washing.

- Where the surface features traces of old paint, remove any parts which are flaking and which are not perfectly adherent, whilst thick coats of lime-based paint or distemper must be removed completely by wetting the surface thoroughly and scraping, or using a water cleaning machine.

- Apply TAMSTUCCO POLVERE by means of successive passes with a plastering trowel to level and fill in order to achieve surface smoothing, or using a putty knife in order to fill the cracks and depressions.

- Proceed with the application of the fixative, chosen on the basis of the type of paint used for the finishing system.

Woodwork:

- Sand lightly in order to remove the raised wood fibres.

- Eliminate any coats of old flaking varnish and coarsen all the surfaces which have already been varnished.

- Remove any resin using the Nitro thinner 5170076.

- Fill any imperfections using TAMSTUCCO POLVERE.

- Sand and, after approx. 6 hours, apply a coat of the

fixative, chosen on the basis of the type of paint used for the finishing system.

APPLICATION INSTRUCTIONS

Air and surface conditions:

Air temperature: Min. +5 C / Max. +35 C.

Relative humidity of the air: <80%.

Temperature of the surface: Min. +5 C / Max. +35 C.

- The product can be applied using a putty knife or plastering trowel.

- Thinning: mix 100 parts of the product with 50-55 parts of water.

- Pot life of the mixture: 1 and a half hours

- Tools should be cleaned immediately after use using water.

- Indicative spreading rate: highly variable depending on the type of surface. With an applied thickness of 400-500 microns, a spreading rate of 1 sq m/kg is obtained. It is advisable to perform a preliminary test on the specific surface in order to determine the actual consumption.

TINTING

STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

Stability in the original closed containers stored at suitable temperatures: 1 year.

SAFETY RULES

Dir. 2004/42/EC not applicable

The product does not require labelling in accordance with 67/548/EEC and 1999/45/EC and its subsequent changes and updates. Use the product in accordance with the hygiene and safety regulations in force; avoid litter with the containers, allow the remains to dry well and treat as special waste. Keep out of the reach of children. Use in an airy place.

For further information consult the safety data sheet.

SPECIFICATION ITEM

Applications, on preprepared interior surfaces, of TAMSTUCCO POLVERE Powder wood or wall filler cod. 9410110 - with a base of fast-drying gypsum, retarders and setting regulators - for levelling imperfections on walls or woodwork.

SAN MARCO GROUP guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.