

FACCIAVISTA PRO

WATER-REPELLENT ACRYL-SILOXANIC SEALANT

code 0730230

DESCRIPTION

FACCIAVISTA PRO is a polysiloxane-based product with high surface penetration and consolidating power, which protects and protects varying types of mineral-based surfaces from crumbling.

FACCIAVISTA PRO prevents both the progressive crumbling of the construction material, provoked by an alternation of freezing and thawing, and the formation of ugly white patches caused by the water-soluble salts appearing on the surface.

As a result of its chemical formula, FACCIAVISTA PRO does not alter the look of the surface, nor its breathability; reacting with the mineral components, it creates a hydrophobic area which does not permit the absorption of water and consequent leaching of salts and efflorescence.

INSTRUCTIONS FOR USE

FACCIAVISTA PRO is suitable for protecting vertical surfaces indoors and outdoors in any climatic and environmental conditions.

It may be applied to absorbent mineral and stone surfaces, concrete, cellular concrete, reinforced concrete, limestone and sandstone, exposed plasterwork and tiles.

It should not be applied over old paint or organic coatings and gypsum.

It should not be applied over non-absorbent surfaces (polished marble, granite).

TECHNICAL SPECIFICATIONS

- Type of Binder: modified siloxanic copolymers.
- Solvents: petroleum distillate.
- Specific gravity per UNI EN ISO 2811-1: 0.80 ± 0.04 kg/l
- Appearance: transparent liquid.
- Drying times (at 25 °C and 65% relative humidity): to touch in 2 hours; to recoat after approx 12 hours.

PREPARING THE SURFACE

Surfaces in stone or brick:

- Dust and clean the surfaces; if there is a patina of dirt, daubs or scales, etc., clean with sandblaster or water under pressure or chemical cleaning. It is advisable to effect a preliminary test to establish the most effective method and type of cleaning.

- If there is mould, first treat the surface with COMBAT 222 Detergent 4810222 and COMBAT 333 Risanante (cleaner) 4810333 (see relative technical sheets).

- Once the surface is dry, apply 2 coats of FACCIAVISTA PRO.

APPLICATION INSTRUCTIONS

Conditions of the surface and surroundings:

Air temperature: Min. +5 °C / Max. +35 °C.

Relative humidity of the air: <80%.

Temperature of the surface to be treated: Min. +5 °C / Max. +35 °C.

Humidity of the surface to be treated: <10%.

- Avoid applying the paint where there is surface

condensation or directly under the sun.

- Tools: brush.

- N. coats: 1-2

- The product is ready for use; only with surfaces that have little porosity, is it recommended that the product be diluted with 15-20% of Diluente Sintetico 5210011 synthetic thinner.

- All tools should be cleaned using Diluente Sintetico 5210011 synthetic thinner immediately after use.

- Indicative coverage: 2-4 sq.m./l. per coat on surfaces of average porosity. It is recommended that a test be effected on the surface to determine the consumption of the product.

- During the application, protect (screen off) surfaces in glass, ceramic and plastic.

TINTING

The product is supplied colourless.

STORAGE

Maximum temperature for storage: +30 °C.

Minimum temperature for storage: +5 °C.

Store in a dry place.

The product should be preferably used within 1 year from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

Limit value EU (Dir. 2004/42/EC)

Cat . H: Binding primers (solvent-base): 750 g/l (2007) / 750 g/l (2010)

FACCIAVISTA PRO Contains max: 750 g/l VOC

Inflammable.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Keep out of the reach of children.

Do not breathe gas/fumes/vapour, spray (appropriate wording to be specified by the manufacturer).

Do not empty into drains.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

contains: heavy hydro-desulphurised naphtha (petroleum)

The product must be moved, used and stored in accordance with current legislation concerning health and safety; after use, do not throw away the container, but allow the contents to dry completely and treat them as special waste. For further information, consult the safety form.

SPECIFICATION ITEM

Water-repellent siloxanic sealant.

Applications, over previously prepared surfaces, of FACCIAVISTA PRO sealant primer, code 0730230, based on siloxanic polymers dissolved in suitable solvent, for the protection of mineral surfaces, with sealing effect on

FACCIAVISTA PRO

WATER-REPELLENT ACRYL-SILOXANIC SEALANT

code 0730230

powdery surfaces.

Supply and application of the material € per sq.m.

SAN MARCO GROUP guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.