

# SBIANCANTE PER LEGNO

WATER BASED LIGHTENING ACTION GEL

Code 1110000

## DESCRIPTION

SBIANCANTE PER LEGNO is a gel product specifically formulated for cleaning and stain removal of not overcoated woodwork which suffered weatherproof.

Its gel formulation, ready to use, ensures rapid and penetrating action, eliminates the gray, stains and dirt without altering the structure of the wood, without discoloring the wood species.

## INSTRUCTIONS FOR USE

It may be applied on:

- Wood surfaces and external objects such as tables, benches, chairs, panels, gazebos, planters etc. etc.

## TECHNICAL SPECIFICATIONS

- Density: 1.05±0.05 kg/l at 20 ° C
- Colour: transparent
- Appearance: gel
- Odour: characteristic
- pH=3
- Shake before using. Do not dilute.

## PREPARING THE SURFACE

Make sure that the wood surface is rough, devoid of finishes. If you need to remove the traces with SVERNICIATORE SM10 cod. 5610014 and possibly smooth with a fine abrasive.

Apply with plenty of SBIANCANTE PER LEGNO by brush, in the direction of the wood fibers, with mechanical action of rubbing.

Leave it for 10-15 minutes. If necessary, rub with a brush with stiff hairs to optimize the cleaning action. Rinse with plenty of water.

Repeat the application over particularly blackening surfaces.

Once the surface got dried apply the selected protection.

## APPLICATION INSTRUCTIONS

Environmental and surface conditions:

Air temperature: Min. +8 °C / Max. +35 °C

Relative Humidity: <75%

Temperature of the surface: Min. +5 °C / Max. +35 °C

-Tools: brush.

-Dilution: Ready to use.

-Nr of coats: apply 1 or more coats until the complete cleaning of the surface.

-Clean tools with water immediately after use.

-Indicative spreading rate: 4-6 sqm / l depending on the dirt and the absorption of the wood.

It is advisable to perform a preliminary test on the specific support surface to determine the consumption.

## TINTING

-----

## STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

## SAFETY RULES

Dir. 2004/42/EC not applicable

Causes serious eye damage. Causes skin irritation.

Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Store out of the reach of children. In case of ingestion, see a physician immediately and show him or her the container or label. Do not dispose of residues in the sewers, waterways or ground. For more information consult the safety data sheet.

## SPECIFICATION ITEM

SBIANCANTE PER LEGNO cod. 111000, water-based regenerating for wood surfaces.

Supply and application of the material € ..... per sqm.

*SAN MARCO GROUP guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.*