

CONTINUO DECO

MINERAL-ORGANIC, TWO-COMPONENT, SPREADABLE-PASTE DECORATIVE COAT

Series 114/115

DESCRIPTION

CONTINUO DECO is a two-component, decorative spreadable paste for coating horizontal and vertical surfaces. It can be coloured with a tintometric system.

The formulation can be adapted to the various needs of modern building and allows for different effects to be achieved, from the flat-and-uniform monolithic to two-tone and textured.

For further information on creating the effects, see the technical application manual.

INSTRUCTIONS FOR USE

CONTINUO DECO guarantees excellent adhesion to the LEVEL_ZERO or BASE primers provided by the CONTINUO system, creating highly customisable horizontal and vertical surfaces with a high aesthetic appeal.

CONTINUO DECO is a particularly versatile product. The working of the pasta optimises on-site time and allows a wide range of aesthetic effects to be obtained with a single product.

TECHNICAL SPECIFICATIONS

CONTINUO DECO COMPONENT A

- Binder type: acrylic copolymer in water emulsion
- Appearance: white paste
- Solvent: water

CONTINUO DECO COMPONENT B

- Binder nature: cement and aggregates.
- Appearance: white powder
- Max. aggregate size: <0.3 mm

CONTINUO DECO MIXTURE A+B

- Mixture ratio: 3:1 by weight
- Specific weight of the mix UNI EN ISO 2811-1: 1.77 ± 0.05 c.a. kg/l
- Working time: about 120 minutes at 25°C, RH=60%.
- Drying (at 25°C and 65% R.H.): to the touch in 60 min; can be painted over after 3 hours (varies depending on ambient conditions and substrate).

PREPARING THE SURFACE

The surface must meet the following requirements:

- must be dry, compact and dust-free. Irregularities due to incorrect application of the substrate can be mitigated by sanding.

APPLICATION INSTRUCTIONS

Ambient and surface conditions:

Ambient temperature: min. +5°C - max. +35 °C

Ambient temperature: min. +5°C - max. +35 °C. - Add to each 15 kg painted pack of CONTINUO DECO A a whole 5 kg pack of CONTINUO DECO B.

- The addition should be done gradually and under slow stirring with drill equipped with a whisk for at least 3 minutes.

- It is possible to add up to 5-8% by weight of water to the mixture.

- The resulting mortar must be uniform, thixotropic and without lumps.

- Tools: stainless steel trowel

- To create particular aesthetic effects with CONTINUO DECO, you must consult the technical application manual.

- No. of layers: 2-3 layers of product depending on the desired aesthetic effect

- Before applying the primer, the surface can be lightly sanded with a random orbital or single brush.

- Clean the equipment with water immediately after use.

- Indicative covering capacity: 1.2-1.5 kg/sq.m in the 2 layers.

The covering capacity is indicative and refers to flat surfaces. Before proceeding, we recommend testing directly on site.

TINTING

The product may be tinted by means of the Color Matching System.

When using multiple batches it is recommended to remix the various products together to avoid slight differences in shading.

STORAGE

Maximum temperature for storage stability: +30 °C

Minimum temperature for storage stability: +5 °C

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

EU limit value (Dir. 2004/42/EC)

Cat. A/I: decorative effect coatings (water-base): 200 g/l (2010)

The product contains max: 200 g/l VOC

Use the product according to current health and safety regulations; after use, do not discard the containers in the environment; allow the residue to dry thoroughly, then treat as special waste. Do not dispose of residues in the sewers, waterways or ground. For more information consult the safety data sheet.

SPECIFICATION ITEM

Decorative coating in spreadable paste for horizontal and vertical surfaces to create CONTINUO decorative systems. Indicative consumption of 1.2 - 1.5 kg/sq.m in the 2 layers. Supply and application of material € per sq.m

SAN MARCO GROUP guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.

CONTINUO DECO

MINERAL-ORGANIC, TWO-COMPONENT, SPREADABLE-PASTE DECORATIVE COAT

Series 114/115